according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Marking ink 4730 P

vellow

12.11.2020 **Revision date:** Version (Revision): 5.0.2 (5.0.1)

Print date: 12.11.2020

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Marking ink 4730 P

yellow (15050500005040)

Unique Formula Identifier (UFI): MYDW-DQG7-HYEM-U2KY

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Industrial marking ink

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Stefan Kupietz GmbH & Co. KG

Chemische Fabrik

Street: August-Wilhelm-Kühnholz-Str. 9 Postal code/city: 26135 Oldenburg **Telephone:** +49(0)441/20 69 50 **Telefax:** +49(0)441 /20 69 520

Information contact: E-Mail: info@kupietz.de

1.4 Emergency telephone number

Poison emergency centre +49-551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3; H226 - Flammable liquids: Category 3; Flammable liquid and vapour.

STOT RE 1; H372 - STOT-repeated exposure: Category 1; Causes damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms





Flame (GHS02) · Health hazard (GHS08)

Signal word

Danger

Hazard components for labelling

NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY; CAS No.: 64742-82-1

Hazard statements

H226 Flammable liquid and vapour.

H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

Page: 1 / 7

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Marking ink 4730 P

yellow

Revision date: 12.11.2020 **Version (Revision):** 5.0.2 (5.0.1)

Print date : 12.11.2020

P314 Get medical advice/attention if you feel unwell.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or

shower].

P403+P235 Store in a well-ventilated place. Keep cool.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY; REACH Registration No.: 01-2119471843-32-xxxx; EC No.: 265-185-

4; CAS No.: 64742-82-1

Weight fraction : < 15 %

Classification 1272/2008 [CLP]: Asp. Tox. 1; H304 STOT RE 1; H372

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove all contaminated clothing.

Following inhalation

Provide fresh air.

In case of skin contact

Wash away with soap and water and rinse.

After eye contact

Flush with plenty of water (10 - 15 min.). Call a physician.

After ingestion

Drink plenty of water.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam , Carbon dioxide (CO2) , Extinguishing powder or Water spray jet .

5.2 Special hazards arising from the substance or mixture

None

5.3 Advice for firefighters

None

5.4 Additional information

Cool endangered containers with water in case of fire.

Page: 2 / 7

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Marking ink 4730 P

yellow

Revision date : 12.11.2020 **Version (Revision) :** 5.0.2 (5.0.1)

Print date : 12.11.2020

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources on account of the organic solvent content and air room well. Do not inhale vapours.

6.2 Environmental precautions

Take up with a liquid absorbing material and proceed according to the waste disposal regulations. Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For cleaning up

Remove mechanically, take-up residues with absorbing material.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Normal precautions taken when handling chemicals should be observed. Only use in locations with adequate suction ventilation.

Protective measures

Measures to prevent fire

Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Do not leave vessels open, earth storage containers.

Hints on joint storage

Store the foodstuffs separately. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

Storage class (TRGS 510): 3

Further information on storage conditions

Store containers tightly closed in a cool well ventilated place.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

2,2`,2``-NITRILOTRIETHANOL; CAS No.: 102-71-6

Limit value type (country of origin): TRGS 900 (D)

Parameter: E: inhalable fraction

Limit value: 1 mg/m³
Peak limitation: 1(I)
Remark: Y
Version: 29.03.2019

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Use tightly fitting safety glasses.

Skin protection

Page: 3 / 7

(EN/D)

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Marking ink 4730 P

yellow

Revision date : 12.11.2020 **Version (Revision) :** 5.0.2 (5.0.1)

Print date : 12.11.2020

Hand protection

Use protective butyl rubber gloves (0,5 mm). Permeation time of glove material: level >= 240 min (4h) EN374

Respiratory protection

Suitable respiratory protection apparatus

Respiratory protection necessary at: aerosol or mist formation. Half-face mask (DIN EN 140) Filtering device (full mask or mouthpiece) with filter: A

General information

The usual precautionary measures for the handling of chemicals have to be observed.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Liquid
Colour : yellow
Odour : characteristic
Safety characteristics

Physical state:

Freezing point:

No data available

Initial boiling point and boiling (1013 hPa) ~ 135 °C

Decomposition temperature : > 200 °C

Flash point : ~ 59 °C Brookfield

Auto-ignition temperature :No data availableLower explosion limit :No data availableUpper explosion limit :No data availableVapour pressure :(50 °C)

 Vapour pressure :
 $(50 \, ^{\circ}\text{C})$
 1100
 hPa

 Density :
 $(20 \, ^{\circ}\text{C})$ ~
 1,248
 g/cm³

 Solvent separation test :
 $(20 \, ^{\circ}\text{C})$ <</td>
 3
 %

 Water solubility :
 $(20 \, ^{\circ}\text{C})$ No data available

 pH :
 ~
 6,9

log P O/W: No data available

Flow time : $(20 \, ^{\circ}\text{C})$ ~ $135 \, \text{s}$ DIN-cup 4 mm

Odour threshold : No data available

Relative vapour density : $(20 \, {}^{\circ}\text{C})$ No data available

Vapourisation rate : No data available

Flammable aerosols:

Oxidising liquids:

No data available.

Explosive properties:

No data available.

9.2 Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

No information available.

Page: 4 / 7

(EN/D)

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Marking ink 4730 P

yellow

Revision date: 12.11.2020 **Version (Revision):** 5.0.2 (5.0.1)

Print date : 12.11.2020

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

None, if handled according to order.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. In connection with inorganic and organic acids, acid chlorides violent reactions can take place and CO2 released. Formation of hydrogen by acids, lyes, moisture possible.

10.6 Hazardous decomposition products

No information available.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute inhalation toxicity

Practical experience/human evidence

Slight narcotic effect. Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea.

SECTION 12: Ecological information

12.1 Toxicity

No information available.

12.2 Persistence and degradability

In case of appropriate conduction into adapted biological purification plants no disturbances have to be expected.

12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

12.4 Mobility in soil

Very high mobility in soil with a negligible tendency to leave the sediment.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

Do not empty into waters or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose according to legislation.

Directive 2008/98/EC (Waste Framework Directive)

After intended use

Waste codes/waste designations according to EWC/AVV

- 080111

Additional information

Contaminated packaging should be residue-free emptying. They can then be recycled after appropriate cleaning (Waste code 080112 contains no organic solvents). Contaminated packaging should be disposed of like the product. (Waste code 150110)

Page: 5 / 7

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Marking ink 4730 P

vellow

12.11.2020 **Revision date:** Version (Revision): 5.0.2 (5.0.1)

Print date: 12.11.2020

SECTION 14: Transport information

14.1 UN number

UN 1263

14.2 UN proper shipping name

Land transport (ADR/RID) PAINT RELATED MATERIAL

Sea transport (IMDG)

PAINT RELATED MATERIAL

Air transport (ICAO-TI / IATA-DGR)

PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

Land transport (ADR/RID)

3 Class(es): Classification code: F1 Hazard identification number (Kemler 30 No.):

Tunnel restriction code: D/E

Special provisions: LQ 5 I · E 1 · Transport in containers with max. 450 litres contents are not subject

to the regulations of ADR/RID.

Hazard label(s):

Sea transport (IMDG)

Class(es): 3 EmS-No.:

F-E / <u>S-E</u>

Special provisions: LQ 5 | · E 1 · IMDG 2.3.2.5 (<= 30 |)

Hazard label(s): 3

Air transport (ICAO-TI / IATA-DGR) Class(es): 3 F 1 **Special provisions:** Hazard label(s): 3

14.4 Packing group

14.5 Environmental hazards

Land transport (ADR/RID): No Sea transport (IMDG): No

Air transport (ICAO-TI / IATA-DGR): No

14.6 Special precautions for user

None

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or 15.1 mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Use restriction according to REACH annex XVII, no.: 3

National regulations

Water hazard class (WGK)

Page: 6 / 7

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Marking ink 4730 P

yellow

Revision date : 12.11.2020 **Version (Revision) :** 5.0.2 (5.0.1)

Print date : 12.11.2020

Classification according to AwSV - Class: 2 (Obviously hazardous to water)

15.2 Chemical safety assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

03. Hazardous ingredients · 15. Water hazard class (WGK)

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

None

^{16.4} Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

See SECTION 2.1 (classification).

16.5 Relevant H- and EUH-phrases (Number and full text)

H304 May be fatal if swallowed and enters airways.

H372 Causes damage to organs through prolonged or repeated exposure.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 7 / 7