# according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Stamping ink 6051 P

black

**Revision date :** 12.11.2020 **Version (Revision) :** 3.1.1 (3.1.0)

**Print date :** 12.11.2020

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier

Stamping ink 6051 P black (15010780001040)

Unique Formula Identifier (UFI): J8CE-1KAD-9XE1-28CW

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses

Industrial marking ink

# 1.3 Details of the supplier of the safety data sheet

# Supplier (manufacturer/importer/only representative/downstream user/distributor)

Stefan Kupietz GmbH & Co. KG

Chemische Fabrik

Street: August-Wilhelm-Kühnholz-Str. 9
Postal code/city: 26135 Oldenburg
Telephone: +49(0)441/20 69 50
Telefax: +49(0)441 /20 69 520

Information contact: E-Mail: info@kupietz.de

## 1.4 Emergency telephone number

Poison emergency centre +49-551-19240

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

None

## 2.2 Label elements

# Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Special rules for supplemental label elements for certain mixtures

EUH210 Safety data sheet available on request.

#### 2.3 Other hazards

None

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### **Hazardous ingredients**

WHITE MINERAL OIL (PETROLEUM); REACH Registration No.: 01-2119487078-27-xxxxx; EC No.: 232-455-8; CAS No.: 8042-

47-5

Weight fraction: < 75 %

Classification 1272/2008 [CLP]: Asp. Tox. 1; H304

Additional information

Full text of H- and EUH-phrases: see section 16.

# **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

Page: 1/6

# according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Stamping ink 6051 P

black

**Revision date:** 12.11.2020 **Version (Revision):** 3.1.1 (3.1.0)

**Print date :** 12.11.2020

#### **General information**

Immediately remove all contaminated clothing.

## **Following inhalation**

Provide fresh air.

## In case of skin contact

Wash away with soap and water and rinse.

#### After eye contact

Flush with plenty of water (10 - 15 min.). Call a physician.

#### **After ingestion**

Drink plenty of water.

# 4.2 Most important symptoms and effects, both acute and delayed

No information available.

# 4.3 Indication of any immediate medical attention and special treatment needed

None

## **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam , Carbon dioxide (CO2) , Extinguishing powder or Water spray jet .

# 5.2 Special hazards arising from the substance or mixture

None

## 5.3 Advice for firefighters

None

# 5.4 Additional information

Cool endangered containers with water in case of fire.

#### **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources on account of the organic solvent content and air room well. Do not inhale vapours.

#### 6.2 Environmental precautions

Take up with a liquid absorbing material and proceed according to the waste disposal regulations. Do not allow to enter into surface water or drains.

# 6.3 Methods and material for containment and cleaning up

# For cleaning up

Remove mechanically, take-up residues with absorbing material.

#### 6.4 Reference to other sections

None

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

Normal precautions taken when handling chemicals should be observed. Only use in locations with adequate suction ventilation.

#### **Protective measures**

Measures to prevent fire

Page: 2 / 6

# according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Stamping ink 6051 P

black

**Revision date :** 12.11.2020 **Version (Revision) :** 3.1.1 (3.1.0)

**Print date :** 12.11.2020

Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking.

## 7.2 Conditions for safe storage, including any incompatibilities

# **Technical measures and storage conditions**

Do not leave vessels open, earth storage containers.

## Hints on joint storage

Store the foodstuffs separately. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

Storage class (TRGS 510): 10

## **Further information on storage conditions**

Store containers tightly closed in a cool well ventilated place.

# 7.3 Specific end use(s)

None

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

#### **Occupational exposure limit values**

WHITE MINERAL OIL (PETROLEUM); CAS No.: 8042-47-5 Limit value type (country of origin): TRGS 900 ( D ) Parameter: A: respirable fraction

Limit value: 5 mg/m³
Peak limitation: 4(II)
Remark: Y
Version: 29.03.2019
2,2`,2``-NITRILOTRIETHANOL; CAS No.: 102-71-6

Limit value type (country of origin): TRGS 900 ( D )
Parameter: E: inhalable fraction

Version: 29.03.2019

# 8.2 Exposure controls

## **Personal protection equipment**

#### **Eye/face protection**

Use tightly fitting safety glasses.

## Skin protection

#### **Hand protection**

Use protective butyl rubber gloves (0,5 mm). Permeation time of glove material: level >= 240 min (4h) EN374

## **Respiratory protection**

# Suitable respiratory protection apparatus

Respiratory protection necessary at: aerosol or mist formation. Half-face mask (DIN EN 140) Filtering device (full mask or mouthpiece) with filter: A

## **General information**

The usual precautionary measures for the handling of chemicals have to be observed.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance: Liquid

Page: 3 / 6

(EN/D)

# according to Regulation (EC) No. 1907/2006 (REACH)



°C

**Trade name :** Stamping ink 6051 P

black

**Revision date :** 12.11.2020 **Version (Revision) :** 3.1.1 (3.1.0)

**Print date :** 12.11.2020

Colour: black
Odour: characteristic
Safety characteristics

Physical state : Liquid
Freezing point : No data available

Initial boiling point and boiling (1013 hPa) > 140

range:

**Decomposition temperature :** > 200 °C

Flash point: > 61 °C Brookfield

Auto-ignition temperature:

Lower explosion limit:

No data available

Upper explosion limit:

No data available

Vapour pressure: (50°C) < 1100 hPa Density: 0,922 g/cm3 ( 20 °C ) ~ Solvent separation test : (20°C) 3 % Water solubility: (20°C) No data available

pH: ~ 7,9
log P O/W: No data available

**Flow time :** (20 °C) ~ 33 s DIN-cup 4 mm

**Odour threshold :** No data available

**Relative vapour density :** (20 °C) No data available **Vapourisation rate :** No data available

Flammable aerosols:

Oxidising liquids:

No data available.

No data available.

Explosive properties:

No data available.

9.2 Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No information available.

#### 10.2 Chemical stability

No information available.

## 10.3 Possibility of hazardous reactions

No information available.

#### 10.4 Conditions to avoid

None, if handled according to order.

# 10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. In connection with inorganic and organic acids, acid chlorides violent reactions can take place and CO2 released. Formation of hydrogen by acids, lyes, moisture possible.

# 10.6 Hazardous decomposition products

No information available.

## **SECTION 11: Toxicological information**

Page: 4 / 6

# according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink 6051 P

black

**Revision date:** 12.11.2020 **Version (Revision):** 3.1.1 (3.1.0)

**Print date :** 12.11.2020

#### 11.1 Information on toxicological effects

#### **Acute toxicity**

#### **Acute inhalation toxicity**

#### Practical experience/human evidence

Slight narcotic effect. Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

No information available.

# 12.2 Persistence and degradability

In case of appropriate conduction into adapted biological purification plants no disturbances have to be expected.

## 12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

## 12.4 Mobility in soil

Very high mobility in soil with a negligible tendency to leave the sediment.

#### 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6 Other adverse effects

No information available.

#### 12.7 Additional ecotoxicological information

Do not empty into waters or drains.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Dispose according to legislation.

#### **Directive 2008/98/EC (Waste Framework Directive)**

#### After intended use

# Waste codes/waste designations according to EWC/AVV

- 080111

#### **Additional information**

Contaminated packaging should be residue-free emptying. They can then be recycled after appropriate cleaning (Waste code 080112 contains no organic solvents). Contaminated packaging should be disposed of like the product. (Waste code 150110)

#### **SECTION 14: Transport information**

#### 14.1 UN number

No dangerous good in sense of these transport regulations.

# 14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

## 14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

#### 14.4 Packing group

No dangerous good in sense of these transport regulations.

# 14.5 Environmental hazards

Page: 5 / 6

# according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Stamping ink 6051 P

black

**Revision date:** 12.11.2020 **Version (Revision):** 3.1.1 (3.1.0)

**Print date :** 12.11.2020

No dangerous good in sense of these transport regulations.

## 14.6 Special precautions for user

None

## **SECTION 15: Regulatory information**

# Safety, health and environmental regulations/legislation specific for the substance or mixture

**National regulations** 

**Technische Anleitung Luft (TA-Luft)** 

Weight fraction (Number 5.2.5. I): < 5 %

Water hazard class (WGK)

Classification according to AwSV - Class: 1 (Slightly hazardous to water)

## 15.2 Chemical safety assessment

No information available.

## **SECTION 16: Other information**

#### 16.1 Indication of changes

03. Hazardous ingredients

#### 16.2 Abbreviations and acronyms

None

#### 16.3 Key literature references and sources for data

None

# Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

See SECTION 2.1 (classification).

# 16.5 Relevant H- and EUH-phrases (Number and full text)

H304 May be fatal if swallowed and enters airways.

# 16.6 Training advice

None

#### 16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.