

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink 8300 P  
dark blue  
**Revision date :** 10.12.2020  
**Print date :** 10.12.2020

**Version (Revision) :** 4.0.1 (4.0.0)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

Stamping ink 8300 P  
dark blue (15036020046040)  
Unique Formula Identifier (UFI): 3SGY-M967-SYET-FGQP

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses**

Industrial marking ink

### 1.3 Details of the supplier of the safety data sheet

**Supplier (manufacturer/importer/only representative/downstream user/distributor)**

Stefan Kupietz GmbH & Co. KG  
Chemische Fabrik

**Street :** August-Wilhelm-Kühnholz-Str. 9

**Postal code/city :** 26135 Oldenburg

**Telephone :** +49(0)441/20 69 50

**Telefax :** +49(0)441 /20 69 520

**Information contact :** E-Mail: info@kupietz.de

### 1.4 Emergency telephone number

Poison emergency centre +49-551-19240

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

Flam. Liq. 2 ; H225 - Flammable liquids : Category 2 ; Highly flammable liquid and vapour.  
Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.  
STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

### 2.2 Label elements

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



Flame (GHS02) · Exclamation mark (GHS07)

**Signal word**

Danger

**Hazard components for labelling**

PROPAN-2-OL ; CAS No. : 67-63-0  
1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2

**Hazard statements**

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink 8300 P  
dark blue  
**Revision date :** 10.12.2020  
**Print date :** 10.12.2020

**Version (Revision) :** 4.0.1 (4.0.0)

P233 Keep container tightly closed.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### 2.3 Other hazards

None

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

2-(2-BUTOXYETHOXY)ETHANOL ; REACH Registration No. : 01-2119475104-44-xxxx ; EC No. : 203-961-6; CAS No. : 112-34-5

Weight fraction : < 45 %  
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

PROPAN-2-OL ; REACH Registration No. : 01-2119457558-25-xxxx ; EC No. : 200-661-7; CAS No. : 67-63-0

Weight fraction : < 20 %  
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336

1-METHOXY-2-PROPANOL ; REACH Registration No. : 01-2119457435-35-xxxx ; EC No. : 203-539-1; CAS No. : 107-98-2

Weight fraction : < 15 %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336

ETHYL ACETATE ; REACH Registration No. : 01-2119475103-46-xxxx ; EC No. : 205-500-4; CAS No. : 141-78-6

Weight fraction : < 10 %  
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336

#### Additional information

Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

Immediately remove all contaminated clothing.

#### Following inhalation

Provide fresh air.

#### In case of skin contact

Wash away with soap and water and rinse.

#### After eye contact

Flush with plenty of water (10 - 15 min.). Call a physician.

#### After ingestion

Drink plenty of water.

### 4.2 Most important symptoms and effects, both acute and delayed

No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

None

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink 8300 P  
dark blue  
**Revision date :** 10.12.2020  
**Print date :** 10.12.2020

**Version (Revision) :** 4.0.1 (4.0.0)

## Suitable extinguishing media

alcohol resistant foam , Carbon dioxide (CO<sub>2</sub>) , Extinguishing powder or Water spray jet .

## 5.2 Special hazards arising from the substance or mixture

None

## 5.3 Advice for firefighters

None

## 5.4 Additional information

Cool endangered containers with water in case of fire.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources on account of the organic solvent content and air room well. Do not inhale vapours.

### 6.2 Environmental precautions

Take up with a liquid absorbing material and proceed according to the waste disposal regulations. Do not allow to enter into surface water or drains.

### 6.3 Methods and material for containment and cleaning up

#### For cleaning up

Remove mechanically, take-up residues with absorbing material.

### 6.4 Reference to other sections

None

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Normal precautions taken when handling chemicals should be observed. Only use in locations with adequate suction ventilation.

#### Protective measures

##### Measures to prevent fire

Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Technical measures and storage conditions

Do not leave vessels open, earth storage containers.

#### Hints on joint storage

Store the foodstuffs separately. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

**Storage class (TRGS 510) :** 3

#### Further information on storage conditions

Store containers tightly closed in a cool well ventilated place.

### 7.3 Specific end use(s)

None

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5

Limit value type (country of origin) : TRGS 900 ( D )

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink 8300 P  
dark blue  
**Revision date :** 10.12.2020  
**Print date :** 10.12.2020

**Version (Revision) :** 4.0.1 (4.0.0)

Limit value : 10 ppm / 67 mg/m<sup>3</sup>  
Peak limitation : 1,5(I)  
Remark : Y  
Version : 29.03.2019  
Limit value type (country of origin) : STEL ( EC )  
Limit value : 15 ppm / 101,2 mg/m<sup>3</sup>  
Version : 20.06.2019  
Limit value type (country of origin) : TWA ( EC )  
Limit value : 10 ppm / 67,5 mg/m<sup>3</sup>  
Version : 20.06.2019  
PROPAN-2-OL ; CAS No. : 67-63-0  
Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 200 ppm / 500 mg/m<sup>3</sup>  
Peak limitation : 2(II)  
Remark : Y  
Version : 29.03.2019  
1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2  
Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 100 ppm / 370 mg/m<sup>3</sup>  
Peak limitation : 2(I)  
Remark : Y  
Version : 29.03.2019  
Limit value type (country of origin) : STEL ( EC )  
Limit value : 150 ppm / 568 mg/m<sup>3</sup>  
Remark : Skin  
Version : 20.06.2019  
Limit value type (country of origin) : TWA ( EC )  
Limit value : 100 ppm / 375 mg/m<sup>3</sup>  
Remark : Skin  
Version : 20.06.2019  
ETHYL ACETATE ; CAS No. : 141-78-6  
Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 200 ppm / 730 mg/m<sup>3</sup>  
Peak limitation : 2(I)  
Remark : Y  
Version : 29.03.2019

### Biological limit values

PROPAN-2-OL ; CAS No. : 67-63-0  
Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Acetone / Whole blood (B) / End of exposure or end of shift  
Limit value : 25 mg/l  
Version : 29.03.2019  
Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Acetone / Urine (U) / End of exposure or end of shift  
Limit value : 25 mg/l  
Version : 29.03.2019  
1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2  
Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : 1-methoxy-2-propanol / Urine (U) / End of exposure or end of shift  
Limit value : 15 mg/l  
Version : 29.03.2019

## 8.2 Exposure controls

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stamping ink 8300 P  
dark blue  
Revision date : 10.12.2020  
Print date : 10.12.2020

Version (Revision) : 4.0.1 (4.0.0)

## Personal protection equipment

### Eye/face protection

Use tightly fitting safety glasses.

### Skin protection

#### Hand protection

Use protective butyl rubber gloves (0,5 mm). Permeation time of glove material: level  $\geq$  240 min (4h) EN374

### Respiratory protection

#### Suitable respiratory protection apparatus

Respiratory protection necessary at: aerosol or mist formation. Half-face mask (DIN EN 140) Filtering device (full mask or mouthpiece) with filter: A

### General information

The usual precautionary measures for the handling of chemicals have to be observed.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : Liquid  
Colour : dark blue  
Odour : characteristic

#### Safety characteristics

Physical state :		Liquid	
Freezing point :		No data available	
Initial boiling point and boiling range :	( 1013 hPa ) ~	93 °C	
Decomposition temperature :	>	200 °C	
Flash point :	~	21 °C	Brookfield
Auto-ignition temperature :		No data available	
Lower explosion limit :		No data available	
Upper explosion limit :		No data available	
Vapour pressure :	( 50 °C ) <	1100 hPa	
Density :	( 20 °C ) ~	0,996 g/cm <sup>3</sup>	
Solvent separation test :	( 20 °C ) <	3 %	
Water solubility :	( 20 °C )	No data available	
pH :	~	3,6	
log P O/W :		No data available	
Flow time :	( 20 °C ) ~	42 s	DIN-cup 4 mm
Odour threshold :		No data available	
Relative vapour density :	( 20 °C )	No data available	
Vapourisation rate :		No data available	
Flammable aerosols :		No data available.	
Oxidising liquids :		No data available.	
Explosive properties :		No data available.	

### 9.2 Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

## SECTION 10: Stability and reactivity

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink 8300 P  
dark blue  
**Revision date :** 10.12.2020  
**Print date :** 10.12.2020

**Version (Revision) :** 4.0.1 (4.0.0)

## 10.1 Reactivity

No information available.

## 10.2 Chemical stability

No information available.

## 10.3 Possibility of hazardous reactions

No information available.

## 10.4 Conditions to avoid

None, if handled according to order.

## 10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. In connection with inorganic and organic acids, acid chlorides violent reactions can take place and CO<sub>2</sub> released. Formation of hydrogen by acids, lyes, moisture possible.

## 10.6 Hazardous decomposition products

No information available.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Acute oral toxicity

Parameter :	LD50 ( 2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5 )
Exposure route :	Oral
Species :	Rat
Effective dose :	6580 mg/kg
Parameter :	LD50 ( PROPAN-2-OL ; CAS No. : 67-63-0 )
Exposure route :	Oral
Species :	Rat
Effective dose :	5840 mg/kg
Parameter :	LD50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )
Exposure route :	Oral
Species :	Rat
Effective dose :	5660 mg/kg
Parameter :	LD50 ( ETHYL ACETATE ; CAS No. : 141-78-6 )
Exposure route :	Oral
Species :	Rabbit
Effective dose :	4935 mg/kg
Parameter :	LD50 ( ETHYL ACETATE ; CAS No. : 141-78-6 )
Exposure route :	Oral
Species :	Rat
Effective dose :	11,3 g/kg

##### Acute dermal toxicity

Parameter :	LD50 ( 2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5 )
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	4120 mg/kg
Parameter :	LD50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	9999,99 mg/kg

##### Acute inhalation toxicity

Parameter :	LC50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )
-------------	--

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink 8300 P  
dark blue  
**Revision date :** 10.12.2020  
**Print date :** 10.12.2020

**Version (Revision) :** 4.0.1 (4.0.0)

Exposure route : Inhalation  
Species : Rat  
Effective dose : 27,596 mg/l  
Exposure time : 6 h  
Parameter : LC50 ( ETHYL ACETATE ; CAS No. : 141-78-6 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 1600 mg/l

### Practical experience/human evidence

Slight narcotic effect. Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea.

## Corrosion

### Skin corrosion/irritation

Parameter : Skin corrosion/irritation ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Species : Rabbit  
Result : Not an irritant

### Serious eye damage/eye irritation

Parameter : Serious eye damage/eye irritation ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Species : Rabbit  
Result : Very minor single cell staining (0,5)

## Respiratory or skin sensitisation

### Skin sensitisation

Parameter : Skin sensitisation ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Species : Guinea pig  
Result : Not sensitising.

## CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

### Carcinogenicity

Parameter : Carcinogenicity ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Exposure route : Carcinogenicity  
Result : Negative.

### Germ cell mutagenicity

#### In vitro mutagenicity

Parameter : In vitro mutagenicity ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Exposure route : In vitro mutagenicity  
Result : Negative.

### Genotoxicity

Parameter : Genotoxicity ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Exposure route : Genotoxicity  
Result : Negative.

### Reproductive toxicity

#### Adverse effects on developmental toxicity

Parameter : One generation reproduction toxicity test ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Exposure route : One generation reproduction toxicity test  
Result : Negative.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity

##### Acute (short-term) fish toxicity

Parameter : LC50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink 8300 P  
dark blue  
**Revision date :** 10.12.2020  
**Print date :** 10.12.2020

**Version (Revision) :** 4.0.1 (4.0.0)

Species : Leuciscus idus (golden orfe)  
Effective dose : 6812 mg/l  
Exposure time : 96 h  
Evaluation : Harmless to fish up to the concentration tested.  
Parameter : LC50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Species : Pimephales promelas (fathead minnow)  
Effective dose : 20800 mg/l  
Exposure time : 96 h  
Evaluation : Harmless to fish up to the concentration tested.  
Parameter : LC50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Species : Oncorhynchus mykiss (Rainbow trout)  
Effective dose : => 1000 mg/l  
Exposure time : 96 h  
Evaluation : Harmless to fish up to the concentration tested.

### Acute (short-term) toxicity to crustacea

Parameter : EC50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Species : Daphnia magna (Big water flea)  
Effective dose : 23300 mg/l  
Exposure time : 48 h  
Evaluation : Harmless to daphnia up to the tested concentration.

### Acute (short-term) toxicity to aquatic algae and cyanobacteria

Parameter : ErC50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Species : Pseudokirchneriella subcapitata  
Effective dose : > 1000 mg/l  
Exposure time : 7 day(s)  
Evaluation : Harmless to algae up to the concentration tested.

### Toxicity to microorganisms

Parameter : EC50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Species : Bacteria toxicity  
Effective dose : 1000 mg/l  
Exposure time : 3 h  
Evaluation : Bacteria toxicity

## 12.2 Persistence and degradability

In case of appropriate conduction into adapted biological purification plants no disturbances have to be expected.

### Biodegradation

Parameter : Biodegradation ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Inoculum : Degree of elimination  
Degradation rate : 96 %  
Evaluation : Readily biodegradable (according to OECD criteria).  
Method : OECD 301E

## 12.3 Bioaccumulative potential

Parameter : Bioconcentration factor (BCF) ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Bioconcentration factor (BCF)  
Value : < 100  
No indication of bioaccumulation potential.

## 12.4 Mobility in soil

Very high mobility in soil with a negligible tendency to leave the sediment.

## 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6 Other adverse effects

No information available.

## 12.7 Additional ecotoxicological information



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink 8300 P  
dark blue  
**Revision date :** 10.12.2020  
**Print date :** 10.12.2020

**Version (Revision) :** 4.0.1 (4.0.0)

Do not empty into waters or drains.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Dispose according to legislation.

#### Directive 2008/98/EC (Waste Framework Directive)

##### After intended use

##### Waste codes/waste designations according to EWC/AVV

- 080111

##### Additional information

Contaminated packaging should be residue-free emptying. They can then be recycled after appropriate cleaning (Waste code 080112 contains no organic solvents). Contaminated packaging should be disposed of like the product. (Waste code 150110)

## SECTION 14: Transport information

### 14.1 UN number

UN 1263

### 14.2 UN proper shipping name

#### Land transport (ADR/RID)

PAINT RELATED MATERIAL

#### Sea transport (IMDG)

PAINT RELATED MATERIAL

#### Air transport (ICAO-TI / IATA-DGR)

PAINT RELATED MATERIAL

### 14.3 Transport hazard class(es)

#### Land transport (ADR/RID)

**Class(es) :** 3  
**Classification code :** F1  
**Hazard identification number (Kemler No.) :** 33  
**Tunnel restriction code :** D/E  
**Special provisions :** 640D · LQ 5 I · E 2 · ADR : III (<= 450 l)  
**Hazard label(s) :** 3

#### Sea transport (IMDG)

**Class(es) :** 3  
**EmS-No. :** F-E / ~~S-E~~  
**Special provisions :** LQ 5 I · E 2 · IMDG 2.3.2.2 (Packing group III <= 450 l)  
**Hazard label(s) :** 3

#### Air transport (ICAO-TI / IATA-DGR)

**Class(es) :** 3  
**Special provisions :** E 2 · IATA 3.3.3.1 (Packing group III <= 30 l)  
**Hazard label(s) :** 3

### 14.4 Packing group

II

### 14.5 Environmental hazards

**Land transport (ADR/RID) :** No  
**Sea transport (IMDG) :** No  
**Air transport (ICAO-TI / IATA-DGR) :** No

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink 8300 P  
dark blue  
**Revision date :** 10.12.2020  
**Print date :** 10.12.2020

**Version (Revision) :** 4.0.1 (4.0.0)

## 14.6 Special precautions for user

None

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

##### Authorisations and/or restrictions on use

##### Restrictions on use

Use restriction according to REACH annex XVII, no. : 3, 40, 55

#### National regulations

##### Water hazard class (WGK)

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

### 15.2 Chemical safety assessment

No information available.

## SECTION 16: Other information

### 16.1 Indication of changes

03. Hazardous ingredients · 08. Occupational exposure limit values · 14. Transport hazard class(es) - Sea transport (IMDG)  
· 15. Restrictions on use · 15. Water hazard class (WGK)

### 16.2 Abbreviations and acronyms

None

### 16.3 Key literature references and sources for data

None

### 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

See SECTION 2.1 (classification).

### 16.5 Relevant H- and EUH-phrases (Number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

### 16.6 Training advice

None

### 16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.