

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink BEROLIN ARISTON P  
white  
**Revision date :** 04.11.2020  
**Print date :** 04.11.2020

**Version (Revision) :** 5.2.1 (5.2.0)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

Stamping ink BEROLIN ARISTON P  
white (1502000021040)  
Unique Formula Identifier (UFI): ARR-WUVM-1XE5-G5DK

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses**

Industrial marking ink

### 1.3 Details of the supplier of the safety data sheet

**Supplier (manufacturer/importer/only representative/downstream user/distributor)**

Stefan Kupietz GmbH & Co. KG  
Chemische Fabrik

**Street :** August-Wilhelm-Kühnholz-Str. 9

**Postal code/city :** 26135 Oldenburg

**Telephone :** +49(0)441/20 69 50

**Telefax :** +49(0)441 /20 69 520

**Information contact :** E-Mail: info@kupietz.de

### 1.4 Emergency telephone number

Poison emergency centre +49-551-19240

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.  
Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

### 2.2 Label elements

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



Flame (GHS02) · Exclamation mark (GHS07)

**Signal word**

Warning

**Hazard statements**

H226 Flammable liquid and vapour.  
H319 Causes serious eye irritation.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink BEROLIN ARISTON P  
white  
**Revision date :** 04.11.2020  
**Print date :** 04.11.2020

**Version (Revision) :** 5.2.1 (5.2.0)

P403+P235 Store in a well-ventilated place. Keep cool.

## 2.3 Other hazards

None

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

ETHANOL ; REACH Registration No. : 01-2119457610-43-xxxx ; EC No. : 200-578-6; CAS No. : 64-17-5

Weight fraction : < 15 %

Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319

BENZYL ALCOHOL ; REACH Registration No. : 01-2119492630-38-xxxx ; EC No. : 202-859-9; CAS No. : 100-51-6

Weight fraction : < 10 %

Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Acute Tox. 4 ; H332 Eye Irrit. 2 ; H319

#### Additional information

Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

Immediately remove all contaminated clothing.

#### Following inhalation

Provide fresh air.

#### In case of skin contact

Wash away with soap and water and rinse.

#### After eye contact

Flush with plenty of water (10 - 15 min.). Call a physician.

#### After ingestion

Drink plenty of water.

### 4.2 Most important symptoms and effects, both acute and delayed

No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

None

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam , Carbon dioxide (CO2) , Extinguishing powder or Water spray jet .

### 5.2 Special hazards arising from the substance or mixture

None

### 5.3 Advice for firefighters

None

### 5.4 Additional information

Cool endangered containers with water in case of fire.

## SECTION 6: Accidental release measures

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink BEROLIN ARISTON P  
white  
**Revision date :** 04.11.2020  
**Print date :** 04.11.2020  
**Version (Revision) :** 5.2.1 (5.2.0)

## 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources on account of the organic solvent content and air room well. Do not inhale vapours.

## 6.2 Environmental precautions

Take up with a liquid absorbing material and proceed according to the waste disposal regulations. Do not allow to enter into surface water or drains.

## 6.3 Methods and material for containment and cleaning up

### For cleaning up

Remove mechanically, take-up residues with absorbing material.

## 6.4 Reference to other sections

None

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Normal precautions taken when handling chemicals should be observed. Only use in locations with adequate suction ventilation.

#### Protective measures

##### Measures to prevent fire

Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Technical measures and storage conditions

Do not leave vessels open, earth storage containers.

#### Hints on joint storage

Store the foodstuffs separately. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

**Storage class (TRGS 510) :** 3

#### Further information on storage conditions

Store containers tightly closed in a cool well ventilated place.

### 7.3 Specific end use(s)

None

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

ETHANOL ; CAS No. : 64-17-5

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 200 ppm / 380 mg/m<sup>3</sup>  
Peak limitation : 4(II)  
Remark : Y  
Version : 29.03.2019

BENZYL ALCOHOL ; CAS No. : 100-51-6

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 5 ppm / 22 mg/m<sup>3</sup>  
Peak limitation : 2(I)  
Remark : H, Y  
Version : 29.03.2019

### 8.2 Exposure controls

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink BEROLIN ARISTON P  
white  
**Revision date :** 04.11.2020  
**Print date :** 04.11.2020

**Version (Revision) :** 5.2.1 (5.2.0)

## Personal protection equipment

### Eye/face protection

Use tightly fitting safety glasses.

### Skin protection

#### Hand protection

Use protective butyl rubber gloves (0,5 mm). Permeation time of glove material: level  $\geq$  240 min (4h) EN374

### Respiratory protection

#### Suitable respiratory protection apparatus

Respiratory protection necessary at: aerosol or mist formation. Half-face mask (DIN EN 140) Filtering device (full mask or mouthpiece) with filter: A

## General information

The usual precautionary measures for the handling of chemicals have to be observed.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

**Appearance :** Liquid  
**Colour :** white  
**Odour :** characteristic

#### Safety characteristics

<b>Physical state :</b>		Liquid	
<b>Freezing point :</b>		No data available	
<b>Initial boiling point and boiling range :</b>	( 1013 hPa ) ~	105 °C	
<b>Decomposition temperature :</b>	>	200 °C	
<b>Flash point :</b>	~	27 °C	Brookfield
<b>Auto-ignition temperature :</b>		No data available	
<b>Lower explosion limit :</b>		No data available	
<b>Upper explosion limit :</b>		No data available	
<b>Vapour pressure :</b>	( 50 °C ) <	1100 hPa	
<b>Density :</b>	( 20 °C ) ~	1,26 g/cm <sup>3</sup>	
<b>Solvent separation test :</b>	( 20 °C ) <	3 %	
<b>Water solubility :</b>	( 20 °C )	No data available	
<b>pH :</b>	~	6,3	
<b>log P O/W :</b>		No data available	
<b>Flow time :</b>	( 20 °C ) ~	31 s	DIN-cup 4 mm
<b>Odour threshold :</b>		No data available	
<b>Relative vapour density :</b>	( 20 °C )	No data available	
<b>Vapourisation rate :</b>		No data available	
<b>Flammable aerosols :</b>		No data available.	
<b>Oxidising liquids :</b>		No data available.	
<b>Explosive properties :</b>		No data available.	

### 9.2 Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

## SECTION 10: Stability and reactivity

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink BEROLIN ARISTON P  
white  
**Revision date :** 04.11.2020  
**Print date :** 04.11.2020  
**Version (Revision) :** 5.2.1 (5.2.0)

## 10.1 Reactivity

No information available.

## 10.2 Chemical stability

No information available.

## 10.3 Possibility of hazardous reactions

No information available.

## 10.4 Conditions to avoid

None, if handled according to order.

## 10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. In connection with inorganic and organic acids, acid chlorides violent reactions can take place and CO<sub>2</sub> released. Formation of hydrogen by acids, lyes, moisture possible.

## 10.6 Hazardous decomposition products

No information available.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Acute oral toxicity

Parameter :	LD50 ( ETHANOL ; CAS No. : 64-17-5 )
Exposure route :	Oral
Species :	Rat
Effective dose :	7600 mg/kg
Parameter :	LD50 ( ETHANOL ; CAS No. : 64-17-5 )
Exposure route :	Oral
Species :	Rabbit
Effective dose :	6300 mg/kg
Parameter :	LD50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )
Exposure route :	Oral
Species :	Rat
Effective dose :	1230 mg/kg
Parameter :	LD50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )
Exposure route :	Oral
Species :	Mouse
Effective dose :	1600 mg/kg

##### Acute dermal toxicity

Parameter :	LD50 ( ETHANOL ; CAS No. : 64-17-5 )
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	20000 mg/kg

##### Acute inhalation toxicity

Parameter :	LC50 ( ETHANOL ; CAS No. : 64-17-5 )
Exposure route :	Inhalation
Species :	Rat
Effective dose :	124,7 mg/l
Exposure time :	4 h
Parameter :	LC50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )
Exposure route :	Inhalation
Species :	Rat
Effective dose :	> 4,178 mg/l

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink BEROLIN ARISTON P  
white  
**Revision date :** 04.11.2020  
**Print date :** 04.11.2020

**Version (Revision) :** 5.2.1 (5.2.0)

Exposure time : 4 h

### Practical experience/human evidence

Slight narcotic effect. Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea.

## Corrosion

### Skin corrosion/irritation

Parameter : Skin corrosion/irritation ( ETHANOL ; CAS No. : 64-17-5 )  
Result : Not an irritant  
Parameter : Skin corrosion/irritation ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Species : Rabbit  
Result : Not an irritant  
Method : OECD 404

### Serious eye damage/eye irritation

Parameter : Serious eye damage/eye irritation ( ETHANOL ; CAS No. : 64-17-5 )  
Result : Strongly irritant  
Parameter : Serious eye damage/eye irritation ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Species : Rabbit  
Result : Irritant  
Method : OECD 405

## Respiratory or skin sensitisation

### Skin sensitisation

Parameter : Skin sensitisation ( ETHANOL ; CAS No. : 64-17-5 )  
Result : Not sensitising.  
Parameter : Skin sensitisation ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Species : Guinea pig  
Result : Not sensitising.  
Method : OECD 406

## CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

### Carcinogenicity

Parameter : Carcinogenicity ( ETHANOL ; CAS No. : 64-17-5 )  
Exposure route : Carcinogenicity  
Result : Negative.

### Germ cell mutagenicity

#### In vitro mutagenicity

Parameter : In vitro mutagenicity ( ETHANOL ; CAS No. : 64-17-5 )  
Exposure route : In vitro mutagenicity  
Result : Negative.

### Reproductive toxicity

#### Adverse effects on developmental toxicity

Parameter : One generation reproduction toxicity test ( ETHANOL ; CAS No. : 64-17-5 )  
Exposure route : One generation reproduction toxicity test  
Result : Negative.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity

##### Acute (short-term) fish toxicity

Parameter : LC50 ( ETHANOL ; CAS No. : 64-17-5 )  
Species : Acute (short-term) fish toxicity  
Effective dose : 11000 mg/l  
Exposure time : 96 h

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink BEROLIN ARISTON P  
white

**Revision date :** 04.11.2020

**Version (Revision) :** 5.2.1 (5.2.0)

**Print date :** 04.11.2020

Parameter : LC50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Species : Pimephales promelas (fathead minnow)  
Effective dose : 460 mg/l  
Exposure time : 96 h

### Acute (short-term) toxicity to crustacea

Parameter : EC50 ( ETHANOL ; CAS No. : 64-17-5 )  
Species : Daphnia magna (Big water flea)  
Effective dose : 9950 mg/l  
Exposure time : 48 h

Parameter : LC50 ( ETHANOL ; CAS No. : 64-17-5 )  
Species : Daphnia magna (Big water flea)  
Effective dose : 9280 mg/l  
Exposure time : 48 h

Parameter : EC50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Species : Daphnia magna (Big water flea)  
Effective dose : 230 mg/l  
Exposure time : 48 h

Method : OECD 202

Parameter : LC50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Species : Daphnia magna (Big water flea)  
Effective dose : 360 mg/l  
Exposure time : 48 h

### Acute (short-term) toxicity to aquatic algae and cyanobacteria

Parameter : EC50 ( ETHANOL ; CAS No. : 64-17-5 )  
Species : Chlorella vulgaris  
Effective dose : 275 mg/l  
Exposure time : 3 h  
Evaluation : Harmless to algae up to the concentration tested.  
Method : OECD 201

Parameter : EC50 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Species : Pseudokirchneriella subcapitata  
Effective dose : 770 mg/l  
Exposure time : 72 h  
Method : OECD 201

Parameter : EC0 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Species : Scenedesmus quadricauda  
Effective dose : 640 mg/l  
Exposure time : 96 h

### Chronic (long-term) algae toxicity

Parameter : EC10 ( ETHANOL ; CAS No. : 64-17-5 )  
Species : Chlorella vulgaris  
Effective dose : 11,5 mg/l  
Exposure time : 3 h  
Evaluation : Chronic (long-term) algae toxicity  
Method : OECD 201

Parameter : NOEC ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Species : Pseudokirchneriella subcapitata  
Effective dose : 310 mg/l  
Exposure time : 72 h  
Method : OECD 201

### Toxicity to microorganisms

Parameter : EC50 ( ETHANOL ; CAS No. : 64-17-5 )  
Species : Bacteria toxicity  
Effective dose : 5800 mg/l

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink BEROLIN ARISTON P  
white  
**Revision date :** 04.11.2020  
**Print date :** 04.11.2020  
**Version (Revision) :** 5.2.1 (5.2.0)

Exposure time : 4 h  
Parameter : EC10 ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Species : Pseudomonas putida  
Effective dose : 658 mg/l  
Exposure time : 16 h

### 12.2 Persistence and degradability

In case of appropriate conduction into adapted biological purification plants no disturbances have to be expected.

#### Biodegradation

Parameter : Biodegradation ( ETHANOL ; CAS No. : 64-17-5 )  
Inoculum : Degree of elimination  
Degradation rate : 84 %  
Test duration : 20 h  
Evaluation : Readily biodegradable (according to OECD criteria).  
Parameter : Biodegradation ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Inoculum : Degree of elimination  
Degradation rate : 92 - 96 %  
Test duration : 28 day(s)  
Evaluation : Readily biodegradable (according to OECD criteria).  
Method : OECD 301C  
Parameter : Biodegradation ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Inoculum : Degree of elimination  
Degradation rate : 95 - 97 %  
Test duration : 21 day(s)  
Evaluation : Readily biodegradable (according to OECD criteria).  
Method : OECD 301A

### 12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

### 12.4 Mobility in soil

Very high mobility in soil with a negligible tendency to leave the sediment.

#### Adsorption

Parameter : Log KOW ( BENZYL ALCOHOL ; CAS No. : 100-51-6 )  
Effective dose : 1,05  
Exposure time : 20 °C

### 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6 Other adverse effects

No information available.

### 12.7 Additional ecotoxicological information

Do not empty into waters or drains.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Dispose according to legislation.

#### Directive 2008/98/EC (Waste Framework Directive)

##### After intended use

##### Waste codes/waste designations according to EWC/AVV

- 080111

##### Additional information

Contaminated packaging should be residue-free emptying. They can then be recycled after appropriate cleaning (Waste code 080112 contains no organic solvents). Contaminated packaging should be disposed of like the product. (Waste code



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stamping ink BEROLIN ARISTON P  
white  
Revision date : 04.11.2020  
Print date : 04.11.2020  
Version (Revision) : 5.2.1 (5.2.0)

150110)

## SECTION 14: Transport information

### 14.1 UN number

UN 1263

### 14.2 UN proper shipping name

Land transport (ADR/RID)

PAINT RELATED MATERIAL

Sea transport (IMDG)

PAINT RELATED MATERIAL

Air transport (ICAO-TI / IATA-DGR)

PAINT RELATED MATERIAL

### 14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3  
Classification code : F1  
Hazard identification number (Kemler No.) : 30  
Tunnel restriction code : D/E  
Special provisions : LQ 5 I · E 1  
Hazard label(s) : 3

Sea transport (IMDG)

Class(es) : 3  
EmS-No. : F-E / S-E  
Special provisions : LQ 5 I · E 1  
Hazard label(s) : 3

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3  
Special provisions : E 1  
Hazard label(s) : 3

### 14.4 Packing group

III

### 14.5 Environmental hazards

Land transport (ADR/RID) : No

Sea transport (IMDG) : No

Air transport (ICAO-TI / IATA-DGR) : No

### 14.6 Special precautions for user

None

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Use restriction according to REACH annex XVII, no. : 3, 40

National regulations

Water hazard class (WGK)

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink BEROLIN ARISTON P  
white  
**Revision date :** 04.11.2020  
**Print date :** 04.11.2020  
**Version (Revision) :** 5.2.1 (5.2.0)

---

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

### 15.2 Chemical safety assessment

No information available.

## SECTION 16: Other information

### 16.1 Indication of changes

03. Hazardous ingredients · 15. Water hazard class (WGK)

### 16.2 Abbreviations and acronyms

None

### 16.3 Key literature references and sources for data

None

### 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

See SECTION 2.1 (classification).

### 16.5 Relevant H- and EUH-phrases (Number and full text)

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

### 16.6 Training advice

None

### 16.7 Additional information

None

---

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---