

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Luminous stamping ink III  
colourless UV blue  
**Revision date :** 12.11.2020  
**Print date :** 12.11.2020

**Version (Revision) :** 13.0.1 (13.0.0)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

Luminous stamping ink III  
colourless UV blue (15034690000038)  
Unique Formula Identifier (UFI): 1YHS-Q8F6-3YE3-7FNN

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses**

Industrial marking ink

### 1.3 Details of the supplier of the safety data sheet

**Supplier (manufacturer/importer/only representative/downstream user/distributor)**

Stefan Kupietz GmbH & Co. KG  
Chemische Fabrik

**Street :** August-Wilhelm-Kühnholz-Str. 9

**Postal code/city :** 26135 Oldenburg

**Telephone :** +49(0)441/20 69 50

**Telefax :** +49(0)441 /20 69 520

**Information contact :** E-Mail: info@kupietz.de

### 1.4 Emergency telephone number

Poison emergency centre +49-551-19240

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

STOT RE 2 ; H373 - STOT-repeated exposure : Category 2 ; May cause damage to organs through prolonged or repeated exposure.

### 2.2 Label elements

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



Flame (GHS02) · Health hazard (GHS08) · Corrosion (GHS05) · Exclamation mark (GHS07)

**Signal word**

Danger

**Hazard components for labelling**

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2

XYLENE ; CAS No. : 1330-20-7

CYCLOHEXANONE ; CAS No. : 108-94-1

**Hazard statements**

H226 Flammable liquid and vapour.

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Luminous stamping ink III  
colourless UV blue  
**Revision date :** 12.11.2020  
**Print date :** 12.11.2020

**Version (Revision) :** 13.0.1 (13.0.0)

H373 May cause damage to organs through prolonged or repeated exposure.  
H318 Causes serious eye damage.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.

### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P310 Immediately call a POISON CENTER/doctor.  
P321 Specific treatment (see information on this label).  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### 2.3 Other hazards

None

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

1-METHOXY-2-PROPANOL ; REACH Registration No. : 01-2119457435-35-xxxx ; EC No. : 203-539-1; CAS No. : 107-98-2

Weight fraction : < 50 %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336

XYLENE ; REACH Registration No. : 01-2119488216-32-xxxx ; EC No. : 215-535-7; CAS No. : 1330-20-7

Weight fraction : < 20 %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT RE 2 ; H373 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 STOT SE 3 ; H335

2-BUTOXYETHYL ACETATE ; REACH Registration No. : 01-2119475112-47-xxxx ; EC No. : 203-933-3; CAS No. : 112-07-2

Weight fraction : < 15 %  
Classification 1272/2008 [CLP] : Acute Tox. 4 ; H312 Acute Tox. 4 ; H332

ETHANOL ; REACH Registration No. : 01-2119457610-43-xxxx ; EC No. : 200-578-6; CAS No. : 64-17-5

Weight fraction : < 10 %  
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319

ETHYLBENZENE ; REACH Registration No. : 01-2119486136-34-xxxx ; EC No. : 202-849-4; CAS No. : 100-41-4

Weight fraction : < 10 %  
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Asp. Tox. 1 ; H304 STOT RE 2 ; H373 Acute Tox. 4 ; H332 Aquatic Chronic 3 ; H412

CYCLOHEXANONE ; REACH Registration No. : 01-2119453616-35-xxxx ; EC No. : 203-631-1; CAS No. : 108-94-1

Weight fraction : < 10 %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315

#### Additional information

Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

Immediately remove all contaminated clothing.

#### Following inhalation

Provide fresh air.

#### In case of skin contact

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Luminous stamping ink III  
colourless UV blue  
**Revision date :** 12.11.2020  
**Print date :** 12.11.2020

**Version (Revision) :** 13.0.1 (13.0.0)

Wash away with soap and water and rinse.

#### **After eye contact**

Flush with plenty of water (10 - 15 min.). Call a physician.

#### **After ingestion**

Drink plenty of water.

#### **4.2 Most important symptoms and effects, both acute and delayed**

No information available.

#### **4.3 Indication of any immediate medical attention and special treatment needed**

None

### **SECTION 5: Firefighting measures**

#### **5.1 Extinguishing media**

##### **Suitable extinguishing media**

alcohol resistant foam , Carbon dioxide (CO2) , Extinguishing powder or Water spray jet .

#### **5.2 Special hazards arising from the substance or mixture**

None

#### **5.3 Advice for firefighters**

None

#### **5.4 Additional information**

Cool endangered containers with water in case of fire.

### **SECTION 6: Accidental release measures**

#### **6.1 Personal precautions, protective equipment and emergency procedures**

Keep away from ignition sources on account of the organic solvent content and air room well. Do not inhale vapours.

#### **6.2 Environmental precautions**

Take up with a liquid absorbing material and proceed according to the waste disposal regulations. Do not allow to enter into surface water or drains.

#### **6.3 Methods and material for containment and cleaning up**

##### **For cleaning up**

Remove mechanically, take-up residues with absorbing material.

#### **6.4 Reference to other sections**

None

### **SECTION 7: Handling and storage**

#### **7.1 Precautions for safe handling**

Normal precautions taken when handling chemicals should be observed. Only use in locations with adequate suction ventilation.

##### **Protective measures**

###### **Measures to prevent fire**

Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking.

#### **7.2 Conditions for safe storage, including any incompatibilities**

##### **Technical measures and storage conditions**

Do not leave vessels open, earth storage containers.

##### **Hints on joint storage**

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Luminous stamping ink III  
colourless UV blue  
**Revision date :** 12.11.2020  
**Print date :** 12.11.2020

**Version (Revision) :** 13.0.1 (13.0.0)

Store the foodstuffs separately. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

**Storage class (TRGS 510) :** 3

### Further information on storage conditions

Store containers tightly closed in a cool well ventilated place.

### 7.3 Specific end use(s)

None

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 100 ppm / 370 mg/m<sup>3</sup>  
Peak limitation : 2(I)  
Remark : Y  
Version : 29.03.2019

Limit value type (country of origin) : STEL ( EC )  
Limit value : 150 ppm / 568 mg/m<sup>3</sup>  
Remark : Skin  
Version : 20.06.2019

Limit value type (country of origin) : TWA ( EC )  
Limit value : 100 ppm / 375 mg/m<sup>3</sup>  
Remark : Skin  
Version : 20.06.2019

XYLENE ; CAS No. : 1330-20-7

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 100 ppm / 440 mg/m<sup>3</sup>  
Peak limitation : 2(II)  
Remark : H  
Version : 29.03.2019

Limit value type (country of origin) : STEL ( EC )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Remark : Skin  
Version : 20.06.2019

Limit value type (country of origin) : TWA ( EC )  
Limit value : 50 ppm / 221 mg/m<sup>3</sup>  
Remark : Skin  
Version : 20.06.2019

2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 10 ppm / 65 mg/m<sup>3</sup>  
Peak limitation : 2(I)  
Remark : H,Y  
Version : 29.03.2019

Limit value type (country of origin) : STEL ( EC )  
Limit value : 50 ppm / 333 mg/m<sup>3</sup>  
Remark : Skin  
Version : 20.06.2019

Limit value type (country of origin) : TWA ( EC )  
Limit value : 20 ppm / 133 mg/m<sup>3</sup>

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Luminous stamping ink III  
colourless UV blue  
**Revision date :** 12.11.2020  
**Print date :** 12.11.2020

**Version (Revision) :** 13.0.1 (13.0.0)

Remark : Skin  
Version : 20.06.2019  
ETHANOL ; CAS No. : 64-17-5  
Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 200 ppm / 380 mg/m<sup>3</sup>  
Peak limitation : 4(II)  
Remark : Y  
Version : 29.03.2019  
ETHYLBENZENE ; CAS No. : 100-41-4  
Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 20 ppm / 88 mg/m<sup>3</sup>  
Peak limitation : 2(II)  
Remark : H, Y  
Version : 29.03.2019  
Limit value type (country of origin) : STEL ( EC )  
Limit value : 200 ppm / 884 mg/m<sup>3</sup>  
Remark : Skin  
Version : 20.06.2019  
Limit value type (country of origin) : TWA ( EC )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Remark : Skin  
Version : 20.06.2019  
CYCLOHEXANONE ; CAS No. : 108-94-1  
Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 20 ppm / 80 mg/m<sup>3</sup>  
Peak limitation : 1(I)  
Remark : H,Y  
Version : 29.03.2019  
Limit value type (country of origin) : STEL ( EC )  
Limit value : 20 ppm / 81,6 mg/m<sup>3</sup>  
Remark : Skin  
Version : 20.06.2019  
Limit value type (country of origin) : TWA ( EC )  
Limit value : 10 ppm / 40,8 mg/m<sup>3</sup>  
Remark : Skin  
Version : 20.06.2019  
2-(2-ETHOXYETHOXY)ETHANOL ; CAS No. : 111-90-0  
Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 6 ppm / 35 mg/m<sup>3</sup>  
Peak limitation : 2(I)  
Remark : Y  
Version : 29.03.2019

## Biological limit values

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2  
Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : 1-methoxy-2-propanol / Urine (U) / End of exposure or end of shift  
Limit value : 15 mg/l  
Version : 29.03.2019  
XYLENE ; CAS No. : 1330-20-7  
Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Methylhippuric acid / Urine (U) / End of exposure or end of shift  
Limit value : 2000 mg/l

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Luminous stamping ink III  
colourless UV blue  
**Revision date :** 12.11.2020  
**Print date :** 12.11.2020

**Version (Revision) :** 13.0.1 (13.0.0)

Version : 29.03.2019  
2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2  
Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Butoxy acetic acid / Urine (U) / At long term exposure: after several previous shifts  
Limit value : 100 mg/l  
Version : 29.03.2019  
Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Butoxy acetic acid / Urine (U) / End of exposure or end of shift ; At long term exposure:  
after several previous shifts  
Limit value : 150 mg/g Kr  
Version : 29.03.2019  
ETHYLBENZENE ; CAS No. : 100-41-4  
Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Mandelic acid + Phenylglyoxyl acid / Urine (U) / End of exposure or end of shift  
Limit value : 250 mg/g Kr  
Version : 29.03.2019

## 8.2 Exposure controls

### Personal protection equipment

#### Eye/face protection

Use tightly fitting safety glasses.

#### Skin protection

##### Hand protection

Use protective butyl rubber gloves (0,5 mm). Permeation time of glove material: level  $\geq$  240 min (4h) EN374

#### Respiratory protection

##### Suitable respiratory protection apparatus

Respiratory protection necessary at: aerosol or mist formation. Half-face mask (DIN EN 140) Filtering device (full mask or mouthpiece) with filter: A

### General information

The usual precautionary measures for the handling of chemicals have to be observed.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

**Colour :** colourless

**Odour :** characteristic

#### Safety characteristics

**Physical state :**

Liquid

**Initial boiling point and boiling range :** ( 1013 hPa ) ~

100 °C

**Flash point :** ~

27 °C Brookfield

**Vapour pressure :** ( 50 °C ) <

1100 hPa

**Density :** ( 20 °C ) ~

0,922 g/cm<sup>3</sup>

**Solvent separation test :** ( 20 °C ) <

3 %

**pH :** ~

3,5

**Flow time :** ( 20 °C ) ~

11 s DIN-cup 4 mm

### 9.2 Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Luminous stamping ink III  
colourless UV blue  
**Revision date :** 12.11.2020  
**Print date :** 12.11.2020

**Version (Revision) :** 13.0.1 (13.0.0)

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No information available.

#### 10.2 Chemical stability

No information available.

#### 10.3 Possibility of hazardous reactions

No information available.

#### 10.4 Conditions to avoid

None, if handled according to order.

#### 10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. In connection with inorganic and organic acids, acid chlorides violent reactions can take place and CO<sub>2</sub> released. Formation of hydrogen by acids, lyes, moisture possible.

#### 10.6 Hazardous decomposition products

No information available.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

###### Acute oral toxicity

Parameter :	LD50 ( XYLENE ; CAS No. : 1330-20-7 )
Exposure route :	Oral
Species :	Rat
Effective dose :	8700 mg/kg
Parameter :	LD50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )
Exposure route :	Oral
Species :	Rat
Effective dose :	3500 mg/kg
Parameter :	LD50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )
Exposure route :	Oral
Species :	Rat
Effective dose :	5660 mg/kg
Parameter :	LD50 ( CYCLOHEXANONE ; CAS No. : 108-94-1 )
Exposure route :	Oral
Species :	Rat
Effective dose :	1620 mg/kg
Parameter :	LD50 ( 2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2 )
Exposure route :	Oral
Species :	Rat
Effective dose :	2400 mg/kg
Parameter :	LD50 ( 2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2 )
Exposure route :	Oral
Species :	Mouse
Effective dose :	3200 mg/kg

###### Acute dermal toxicity

Parameter :	LD50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	9999,99 mg/kg

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Luminous stamping ink III  
colourless UV blue  
**Revision date :** 12.11.2020  
**Print date :** 12.11.2020

**Version (Revision) :** 13.0.1 (13.0.0)

Parameter : LD50 ( CYCLOHEXANONE ; CAS No. : 108-94-1 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : 1000 mg/kg  
Parameter : LD50 ( 2-BUTOXYETHYL ACETATE ; CAS No. : 112-07-2 )  
Exposure route : Dermal  
Species : Rat  
Effective dose : 1580 mg/kg  
Parameter : LD50 ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : 2000 mg/kg  
Parameter : LD50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : 5000 mg/kg

### Acute inhalation toxicity

Parameter : LC50 ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 6350 mg/l  
Parameter : LC50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 27,596 mg/l  
Exposure time : 6 h

### Practical experience/human evidence

Slight narcotic effect. Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea.

## Corrosion

### Skin corrosion/irritation

Parameter : Skin corrosion/irritation ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Species : Rabbit  
Result : Not an irritant  
Parameter : Skin corrosion/irritation ( ETHANOL ; CAS No. : 64-17-5 )  
Result : Not an irritant

### Serious eye damage/eye irritation

Parameter : Serious eye damage/eye irritation ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Species : Rabbit  
Result : Very minor single cell staining (0,5)  
Parameter : Serious eye damage/eye irritation ( ETHANOL ; CAS No. : 64-17-5 )  
Result : Strongly irritant

## Respiratory or skin sensitisation

### Skin sensitisation

Parameter : Skin sensitisation ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Species : Guinea pig  
Result : Not sensitising.  
Parameter : Skin sensitisation ( ETHANOL ; CAS No. : 64-17-5 )  
Result : Not sensitising.

## CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

### Carcinogenicity

Parameter : Carcinogenicity ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Exposure route : Carcinogenicity



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Luminous stamping ink III  
colourless UV blue  
**Revision date :** 12.11.2020  
**Version (Revision) :** 13.0.1 (13.0.0)  
**Print date :** 12.11.2020

**Result :** Negative.  
**Parameter :** Carcinogenicity ( ETHANOL ; CAS No. : 64-17-5 )  
**Exposure route :** Carcinogenicity  
**Result :** Negative.

## Germ cell mutagenicity

### In vitro mutagenicity

**Parameter :** In vitro mutagenicity ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
**Exposure route :** In vitro mutagenicity  
**Result :** Negative.  
**Parameter :** In vitro mutagenicity ( ETHANOL ; CAS No. : 64-17-5 )  
**Exposure route :** In vitro mutagenicity  
**Result :** Negative.

## Genotoxicity

**Parameter :** Genotoxicity ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
**Exposure route :** Genotoxicity  
**Result :** Negative.

## Reproductive toxicity

### Adverse effects on developmental toxicity

**Parameter :** One generation reproduction toxicity test ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
**Exposure route :** One generation reproduction toxicity test  
**Result :** Negative.  
**Parameter :** One generation reproduction toxicity test ( ETHANOL ; CAS No. : 64-17-5 )  
**Exposure route :** One generation reproduction toxicity test  
**Result :** Negative.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity

##### Acute (short-term) fish toxicity

**Parameter :** LC50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
**Species :** Leuciscus idus (golden orfe)  
**Effective dose :** 6812 mg/l  
**Exposure time :** 96 h  
**Evaluation :** Harmless to fish up to the concentration tested.  
**Parameter :** LC50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
**Species :** Pimephales promelas (fathead minnow)  
**Effective dose :** 20800 mg/l  
**Exposure time :** 96 h  
**Evaluation :** Harmless to fish up to the concentration tested.  
**Parameter :** LC50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
**Species :** Oncorhynchus mykiss (Rainbow trout)  
**Effective dose :** => 1000 mg/l  
**Exposure time :** 96 h  
**Evaluation :** Harmless to fish up to the concentration tested.  
**Parameter :** LC50 ( ETHANOL ; CAS No. : 64-17-5 )  
**Species :** Acute (short-term) fish toxicity  
**Effective dose :** 11000 mg/l  
**Exposure time :** 96 h

##### Acute (short-term) toxicity to crustacea

**Parameter :** EC50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
**Species :** Daphnia magna (Big water flea)

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Luminous stamping ink III  
colourless UV blue

**Revision date :** 12.11.2020

**Version (Revision) :** 13.0.1 (13.0.0)

**Print date :** 12.11.2020

Effective dose : 23300 mg/l  
Exposure time : 48 h  
Evaluation : Harmless to daphnia up to the tested concentration.

Parameter : EC50 ( ETHANOL ; CAS No. : 64-17-5 )  
Species : Daphnia magna (Big water flea)  
Effective dose : 9950 mg/l  
Exposure time : 48 h  
Parameter : LC50 ( ETHANOL ; CAS No. : 64-17-5 )  
Species : Daphnia magna (Big water flea)  
Effective dose : 9280 mg/l  
Exposure time : 48 h

### Acute (short-term) toxicity to aquatic algae and cyanobacteria

Parameter : ErC50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Species : Pseudokirchneriella subcapitata  
Effective dose : > 1000 mg/l  
Exposure time : 7 day(s)  
Evaluation : Harmless to algae up to the concentration tested.

Parameter : EC50 ( ETHANOL ; CAS No. : 64-17-5 )  
Species : Chlorella vulgaris  
Effective dose : 275 mg/l  
Exposure time : 3 h  
Evaluation : Harmless to algae up to the concentration tested.  
Method : OECD 201

### Chronic (long-term) algae toxicity

Parameter : EC10 ( ETHANOL ; CAS No. : 64-17-5 )  
Species : Chlorella vulgaris  
Effective dose : 11,5 mg/l  
Exposure time : 3 h  
Evaluation : Chronic (long-term) algae toxicity  
Method : OECD 201

### Toxicity to microorganisms

Parameter : EC50 ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Species : Bacteria toxicity  
Effective dose : 1000 mg/l  
Exposure time : 3 h  
Evaluation : Bacteria toxicity

Parameter : EC50 ( ETHANOL ; CAS No. : 64-17-5 )  
Species : Bacteria toxicity  
Effective dose : 5800 mg/l  
Exposure time : 4 h

## 12.2 Persistence and degradability

In case of appropriate conduction into adapted biological purification plants no disturbances have to be expected.

### Biodegradation

Parameter : Biodegradation ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Inoculum : Degree of elimination  
Degradation rate : 96 %  
Evaluation : Readily biodegradable (according to OECD criteria).  
Method : OECD 301E

Parameter : Biodegradation ( ETHANOL ; CAS No. : 64-17-5 )  
Inoculum : Degree of elimination  
Degradation rate : 84 %  
Test duration : 20 h  
Evaluation : Readily biodegradable (according to OECD criteria).

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Luminous stamping ink III  
colourless UV blue  
**Revision date :** 12.11.2020  
**Print date :** 12.11.2020

**Version (Revision) :** 13.0.1 (13.0.0)

## 12.3 Bioaccumulative potential

**Parameter :** Bioconcentration factor (BCF) ( 1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2 )  
Bioconcentration factor (BCF)  
**Value :** < 100  
No indication of bioaccumulation potential.

## 12.4 Mobility in soil

Very high mobility in soil with a negligible tendency to leave the sediment.

## 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6 Other adverse effects

No information available.

## 12.7 Additional ecotoxicological information

Do not empty into waters or drains.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Dispose according to legislation.

#### Directive 2008/98/EC (Waste Framework Directive)

##### After intended use

##### Waste codes/waste designations according to EWC/AVV

- 080111

##### Additional information

Contaminated packaging should be residue-free emptying. They can then be recycled after appropriate cleaning (Waste code 080112 contains no organic solvents). Contaminated packaging should be disposed of like the product. (Waste code 150110)

## SECTION 14: Transport information

### 14.1 UN number

UN 1263

### 14.2 UN proper shipping name

#### Land transport (ADR/RID)

PAINT RELATED MATERIAL

#### Sea transport (IMDG)

PAINT RELATED MATERIAL

#### Air transport (ICAO-TI / IATA-DGR)

PAINT RELATED MATERIAL

### 14.3 Transport hazard class(es)

#### Land transport (ADR/RID)

**Class(es) :** 3  
**Classification code :** F1  
**Hazard identification number (Kemler No.) :** 30  
**Tunnel restriction code :** D/E  
**Special provisions :** LQ 5 | E 1  
**Hazard label(s) :** 3

#### Sea transport (IMDG)

**Class(es) :** 3  
**EmS-No. :** F-E / S-E

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Luminous stamping ink III  
colourless UV blue  
**Revision date :** 12.11.2020  
**Print date :** 12.11.2020

**Version (Revision) :** 13.0.1 (13.0.0)

**Special provisions :** LQ 5 | · E 1  
**Hazard label(s) :** 3  
**Air transport (ICAO-TI / IATA-DGR)**  
**Class(es) :** 3  
**Special provisions :** E 1  
**Hazard label(s) :** 3

#### 14.4 Packing group

III

#### 14.5 Environmental hazards

**Land transport (ADR/RID) :** No  
**Sea transport (IMDG) :** No  
**Air transport (ICAO-TI / IATA-DGR) :** No

#### 14.6 Special precautions for user

None

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU legislation

###### Authorisations and/or restrictions on use

###### Restrictions on use

Use restriction according to REACH annex XVII, no. : 3, 40

##### National regulations

###### Water hazard class (WGK)

Classification according to AwSV - Class : 2 (Obviously hazardous to water)

#### 15.2 Chemical safety assessment

No information available.

### SECTION 16: Other information

#### 16.1 Indication of changes

03. Hazardous ingredients · 08. Occupational exposure limit values

#### 16.2 Abbreviations and acronyms

None

#### 16.3 Key literature references and sources for data

None

#### 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

See SECTION 2.1 (classification).

#### 16.5 Relevant H- and EUH-phrases (Number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Luminous stamping ink III  
colourless UV blue  
**Revision date :** 12.11.2020  
**Print date :** 12.11.2020

**Version (Revision) :** 13.0.1 (13.0.0)

---

H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

### 16.6 Training advice

None

### 16.7 Additional information

None

---

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---