

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stamping ink R 9
dark blue
Revision date : 03.08.2020
Print date : 05.08.2020

Version (Revision) : 17.1.1 (17.1.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Stamping ink R 9
dark blue (15035000046038)
Unique Formula Identifier (UFI): FY42-T91S-NYE6-F4X9

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Industrial marking ink

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Stefan Kupietz GmbH & Co. KG
Chemische Fabrik

Street : August-Wilhelm-Kühnholz-Str. 9

Postal code/city : 26135 Oldenburg

Telephone : +49(0)441/20 69 50

Telefax : +49(0)441 /20 69 520

Information contact : E-Mail: info@kupietz.de

1.4 Emergency telephone number

Poison emergency centre +49-551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.
Repr. 1B ; H360 - Reproductive toxicity : Category 1B ; May damage fertility or the unborn child.
STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.
Aquatic Chronic 2 ; H411 - Hazardous to the aquatic environment : Chronic 2 ; Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02) · Health hazard (GHS08) · Environment (GHS09) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2
C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3

Hazard statements

H226 Flammable liquid and vapour.
H360 May damage fertility or the unborn child.
H336 May cause drowsiness or dizziness.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stamping ink R 9
dark blue
Revision date : 03.08.2020
Print date : 05.08.2020

Version (Revision) : 17.1.1 (17.1.0)

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P312 Call a POISON CENTER/doctor if you feel unwell.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

(2-METHOXYMETHYLETHOXY)PROPANOL ; REACH Registration No. : 01-2119450011-60-xxxx ; EC No. : 252-104-2; CAS No. : 34590-94-8

Weight fraction : < 55 %
Classification 1272/2008 [CLP] : Substance with a Community workplace exposure limit

1-METHOXY-2-PROPANOL ; REACH Registration No. : 01-2119457435-35-xxxx ; EC No. : 203-539-1; CAS No. : 107-98-2

Weight fraction : < 30 %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336

Basic Blue 7 derivate ; REACH Registration No. : 01-2119849083-38-0000 ; EC No. : 700-579-6

Weight fraction : < 10 %
Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Eye Irrit. 2 ; H319 STOT SE 3 ; H335 Aquatic Chronic 1 ; H410

C.I. SOLVENT BLUE 70 ; EC No. : 304-661-9; CAS No. : 94277-77-7

Weight fraction : < 2,5 %
Classification 1272/2008 [CLP] : Aquatic Chronic 3 ; H412

C.I. SOLVENT BLACK 29 ; EC No. : 403-720-7; CAS No. : 117527-94-3

Weight fraction : < 1 %
Classification 1272/2008 [CLP] : Repr. 1B ; H360 Aquatic Chronic 2 ; H411

Xanthene dye; CI.45160; similar C.I. Basic Red 1 ; REACH Registration No. : 01-2119935914-30-xxxx ; EC No. : 700-761-5; CAS No. : 26694-69-9

Weight fraction : < 0,5 %
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove all contaminated clothing.

Following inhalation

Provide fresh air.

In case of skin contact

Wash away with soap and water and rinse.

After eye contact

Flush with plenty of water (10 - 15 min.). Call a physician.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stamping ink R 9
dark blue
Revision date : 03.08.2020
Print date : 05.08.2020

Version (Revision) : 17.1.1 (17.1.0)

After ingestion

Drink plenty of water.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam , Carbon dioxide (CO₂) , Extinguishing powder or Water spray jet .

5.2 Special hazards arising from the substance or mixture

None

5.3 Advice for firefighters

None

5.4 Additional information

Cool endangered containers with water in case of fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources on account of the organic solvent content and air room well. Do not inhale vapours.

6.2 Environmental precautions

Take up with a liquid absorbing material and proceed according to the waste disposal regulations. Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For cleaning up

Remove mechanically, take-up residues with absorbing material.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Normal precautions taken when handling chemicals should be observed. Only use in locations with adequate suction ventilation.

Protective measures

Measures to prevent fire

Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Do not leave vessels open, earth storage containers.

Hints on joint storage

Store the foodstuffs separately. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

Storage class (TRGS 510) : 3

Further information on storage conditions

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stamping ink R 9
dark blue
Revision date : 03.08.2020
Print date : 05.08.2020

Version (Revision) : 17.1.1 (17.1.0)

Store containers tightly closed in a cool well ventilated place.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

(2-METHOXYMETHYLETHOXY)PROPANOL ; CAS No. : 34590-94-8

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 50 ppm / 310 mg/m³
Peak limitation : 1(I)
Version : 29.03.2019

Limit value type (country of origin) : TWA (EC)
Limit value : 50 ppm / 308 mg/m³
Remark : Skin
Version : 20.06.2019

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 100 ppm / 370 mg/m³
Peak limitation : 2(I)
Remark : Y
Version : 29.03.2019

Limit value type (country of origin) : STEL (EC)
Limit value : 150 ppm / 568 mg/m³
Remark : Skin
Version : 20.06.2019

Limit value type (country of origin) : TWA (EC)
Limit value : 100 ppm / 375 mg/m³
Remark : Skin
Version : 20.06.2019

Biological limit values

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2

Limit value type (country of origin) : TRGS 903 (D)
Parameter : 1-methoxy-2-propanol / Urine (U) / End of exposure or end of shift
Limit value : 15 mg/l
Version : 29.03.2019

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Use tightly fitting safety glasses.

Skin protection

Hand protection

Use protective butyl rubber gloves (0,5 mm). Permeation time of glove material: level >= 240 min (4h) EN374

Respiratory protection

Suitable respiratory protection apparatus

Respiratory protection necessary at: aerosol or mist formation. Half-face mask (DIN EN 140) Filtering device (full mask or mouthpiece) with filter: A

General information

The usual precautionary measures for the handling of chemicals have to be observed.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stamping ink R 9
dark blue
Revision date : 03.08.2020
Print date : 05.08.2020

Version (Revision) : 17.1.1 (17.1.0)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Liquid
Colour : dark blue
Odour : characteristic

Safety characteristics

Physical state :		Liquid	
Freezing point :		No data available	
Initial boiling point and boiling range :	(1013 hPa) ~	138 °C	
Decomposition temperature :	>	200 °C	
Flash point :	~	47 °C	Brookfield
Auto-ignition temperature :		No data available	
Lower explosion limit :		No data available	
Upper explosion limit :		No data available	
Vapour pressure :	(50 °C) <	1100 hPa	
Density :	(20 °C) ~	0,985 g/cm ³	
Solvent separation test :	(20 °C) <	3 %	
Water solubility :	(20 °C)	No data available	
pH :	~	3,8	
log P O/W :		No data available	
Flow time :	(20 °C) ~	14 s	DIN-cup 4 mm
Odour threshold :		No data available	
Relative vapour density :	(20 °C)	No data available	
Vapourisation rate :		No data available	
Flammable aerosols :		No data available.	
Oxidising liquids :		No data available.	
Explosive properties :		No data available.	

9.2 Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

No information available.

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

None, if handled according to order.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. In connection with inorganic and organic acids, acid chlorides violent reactions can take place and CO₂ released. Formation of hydrogen by acids, lyes, moisture possible.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stamping ink R 9
dark blue
Revision date : 03.08.2020
Print date : 05.08.2020

Version (Revision) : 17.1.1 (17.1.0)

10.6 Hazardous decomposition products

No information available.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute oral toxicity

Parameter : LD50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route : Oral
Species : Rat
Effective dose : 5660 mg/kg

Acute dermal toxicity

Parameter : LD50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route : Dermal
Species : Rabbit
Effective dose : 9999,99 mg/kg

Acute inhalation toxicity

Parameter : LC50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route : Inhalation
Species : Rat
Effective dose : 27,596 mg/l
Exposure time : 6 h

Practical experience/human evidence

Slight narcotic effect. Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea.

Corrosion

Skin corrosion/irritation

Parameter : Skin corrosion/irritation (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Species : Rabbit
Result : Not an irritant
Parameter : Skin corrosion/irritation (Basic Blue 7 derivate)
Result : Not an irritant
Method : OECD 404
Parameter : Skin corrosion/irritation (C.I. SOLVENT BLUE 70 ; CAS No. : 94277-77-7)
Species : Rabbit
Result : No erythema (redness).
Parameter : Skin corrosion/irritation (C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3)
Species : Rabbit
Method : OECD 404
Parameter : Skin corrosion/irritation (Xanthene dye; CI.45160; similar C.I. Basic Red 1 ; CAS No. : 26694-69-9)
Species : Guinea pig
Method : OECD 404

Serious eye damage/eye irritation

Parameter : Serious eye damage/eye irritation (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Species : Rabbit
Result : Very minor single cell staining (0,5)
Parameter : Serious eye damage/eye irritation (Basic Blue 7 derivate)
Species : Rabbit
Result : Causes serious eye irritation
Method : OECD 405
Parameter : Serious eye damage/eye irritation (C.I. SOLVENT BLUE 70 ; CAS No. : 94277-77-7)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stamping ink R 9
dark blue
Revision date : 03.08.2020
Print date : 05.08.2020

Version (Revision) : 17.1.1 (17.1.0)

Species : Rabbit
Result : No conjunctival redness.
Parameter : Serious eye damage/eye irritation (C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3)
Species : Rabbit
Method : OECD 404
Parameter : Serious eye damage/eye irritation (Xanthene dye; CI.45160; similar C.I. Basic Red 1 ; CAS No. : 26694-69-9)
Species : Rabbit

Respiratory or skin sensitisation

Skin sensitisation

Parameter : Skin sensitisation (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Species : Guinea pig
Result : Not sensitising.
Parameter : Skin sensitisation (Basic Blue 7 derivate)
Result : Not sensitising.
Method : OECD 406
Parameter : Skin sensitisation (C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3)
Species : Guinea pig
Method : OECD 406

Sensitisation to the respiratory tract

Parameter : Sensitisation to the respiratory tract (Basic Blue 7 derivate)
Result : May cause sensitization by inhalation.
Method : OECD 406
Parameter : Sensitisation to the respiratory tract (C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3)
Species : Guinea pig
Method : OECD 406

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

Parameter : Carcinogenicity (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route : Carcinogenicity
Result : Negative.
Parameter : Carcinogenicity (Basic Blue 7 derivate)
Exposure route : Carcinogenicity
Species : Carcinogenicity
Result : Ames test negative.
Method : OECD 471 (Ames test)

Germ cell mutagenicity

In vitro mutagenicity

Parameter : In vitro mutagenicity (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route : In vitro mutagenicity
Result : Negative.

Genotoxicity

Parameter : Genotoxicity (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route : Genotoxicity
Result : Negative.

Reproductive toxicity

Adverse effects on developmental toxicity

Parameter : One generation reproduction toxicity test (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Exposure route : One generation reproduction toxicity test
Result : Negative.

STOT-repeated exposure STOT RE 1 and 2

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stamping ink R 9
dark blue
Revision date : 03.08.2020
Print date : 05.08.2020

Version (Revision) : 17.1.1 (17.1.0)

Parameter : STOT RE 1 and 2 (C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3)
Exposure route : STOT RE 1 and 2
Result : STOT RE 1 and 2
Source : STOT RE 1 and 2

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : LC50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Species : Leuciscus idus (golden orfe)
Effective dose : 6812 mg/l
Exposure time : 96 h
Evaluation : Harmless to fish up to the concentration tested.

Parameter : LC50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Species : Pimephales promelas (fathead minnow)
Effective dose : 20800 mg/l
Exposure time : 96 h
Evaluation : Harmless to fish up to the concentration tested.

Parameter : LC50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Species : Oncorhynchus mykiss (Rainbow trout)
Effective dose : => 1000 mg/l
Exposure time : 96 h
Evaluation : Harmless to fish up to the concentration tested.

Parameter : LC50 (C.I. SOLVENT BLUE 70 ; CAS No. : 94277-77-7)
Species : Brachydanio rerio (zebra-fish)
Effective dose : 10 - 100 mg/l
Exposure time : 96 h

Parameter : LC50 (C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3)
Species : Cyprinus carpio (Common Carp)
Effective dose : 1 - 10 mg/l
Exposure time : 96 h

Acute (short-term) toxicity to crustacea

Parameter : EC50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Species : Daphnia magna (Big water flea)
Effective dose : 23300 mg/l
Exposure time : 48 h
Evaluation : Harmless to daphnia up to the tested concentration.

Parameter : EC50 (Basic Blue 7 derivat)
Species : Daphnia magna (Big water flea)
Effective dose : ~ 0,047 mg/l
Exposure time : 48 h
Method : ISO 6341

Parameter : EC50 (C.I. SOLVENT BLUE 70 ; CAS No. : 94277-77-7)
Species : Daphnia magna (Big water flea)
Effective dose : 65,3 mg/l
Exposure time : 48 h

Parameter : EC50 (Xanthene dye; CI.45160; similar C.I. Basic Red 1 ; CAS No. : 26694-69-9)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Chronic (long-term) daphnia toxicity
Effective dose : 1,8 mg/l
Exposure time : 48 h

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stamping ink R 9
dark blue
Revision date : 03.08.2020
Print date : 05.08.2020

Version (Revision) : 17.1.1 (17.1.0)

Method : OECD 202

Chronic (long-term) toxicity to crustacea

Parameter : Chronic (long-term) daphnia toxicity (Basic Blue 7 derivate)
Species : Daphnia magna (Big water flea)
Effective dose : 0,047 mg/l
Exposure time : 48 h
Method : ISO 6341

Acute (short-term) toxicity to aquatic algae and cyanobacteria

Parameter : ErC50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Species : Pseudokirchneriella subcapitata
Effective dose : > 1000 mg/l
Exposure time : 7 day(s)
Evaluation : Harmless to algae up to the concentration tested.

Parameter : EC0 (Basic Blue 7 derivate)
Species : Pseudokirchneriella subcapitata
Effective dose : > 12,6 mg/l
Exposure time : 72 h
Method : ISO 8692

Parameter : EC50 (C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3)
Species : Scenedesmus subspicatus
Effective dose : > 100 mg/l
Exposure time : 72 h

Parameter : EC0 (C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3)
Species : Daphnia magna (Big water flea)
Effective dose : > 1000 mg/l
Exposure time : 24 h
Method : OECD 201

Parameter : EC50 (Xanthene dye; CI.45160; similar C.I. Basic Red 1 ; CAS No. : 26694-69-9)
Species : Pseudokirchneriella subcapitata
Evaluation parameter : Acute (short-term) algae toxicity
Effective dose : 1,4 mg/l
Exposure time : 72 h
Method : OECD 201

Toxicity to microorganisms

Parameter : EC50 (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Species : Bacteria toxicity
Effective dose : 1000 mg/l
Exposure time : 3 h
Evaluation : Bacteria toxicity

Sewage treatment plant

Parameter : EC20 (C.I. SOLVENT BLUE 70 ; CAS No. : 94277-77-7)
Inoculum : Activated sludge
Evaluation parameter : Effects in sewage plants
Effective dose : > 1000 mg/l
Exposure time : 0,5 h
Evaluation : Depending on local conditions and existing concentrations, in the case of discharge in biological sewage plants, problems in the decomposition activity of activated sludge are possible.

Method : OECD 209

Source : Effects in sewage plants

Parameter : EC50 (C.I. SOLVENT BLACK 29 ; CAS No. : 117527-94-3)
Inoculum : Activated sludge
Effective dose : > 100 mg/l
Exposure time : 3 h

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stamping ink R 9
dark blue
Revision date : 03.08.2020
Print date : 05.08.2020

Version (Revision) : 17.1.1 (17.1.0)

Method : ISO 8192

12.2 Persistence and degradability

In case of appropriate conduction into adapted biological purification plants no disturbances have to be expected.

Biodegradation

Parameter :	Biodegradation (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Inoculum :	Degree of elimination
Degradation rate :	96 %
Evaluation :	Readily biodegradable (according to OECD criteria).
Method :	OECD 301E
Parameter :	Biodegradation (Basic Blue 7 derivate)
Inoculum :	Biodegradation
Evaluation :	Not readily biodegradable (according to OECD criteria)
Method :	Biodegradation
Parameter :	Biodegradation (Xanthene dye; CI.45160; similar C.I. Basic Red 1 ; CAS No. : 26694-69-9)
Inoculum :	Degree of elimination
Evaluation parameter :	Biodegradation
Degradation rate :	27 %
Test duration :	28 t/a
Method :	OECD 301B

12.3 Bioaccumulative potential

Parameter :	Bioconcentration factor (BCF) (1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2)
Value :	Bioconcentration factor (BCF) < 100
Parameter :	Partition coefficient n-octanol /water (log P O/W) (Basic Blue 7 derivate)
Value :	Partition coefficient n-octanol /water (log P O/W) ~ 4,27
Method :	Estimated

No indication of bioaccumulation potential.

12.4 Mobility in soil

Very high mobility in soil with a negligible tendency to leave the sediment.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

Do not empty into waters or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose according to legislation.

Directive 2008/98/EC (Waste Framework Directive)

After intended use

Waste codes/waste designations according to EWC/AVV

- 080111

Additional information

Contaminated packaging should be residue-free emptying. They can then be recycled after appropriate cleaning (Waste code 080112 contains no organic solvents). Contaminated packaging should be disposed of like the product. (Waste code 150110)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stamping ink R 9
dark blue
Revision date : 03.08.2020
Print date : 05.08.2020

Version (Revision) : 17.1.1 (17.1.0)

SECTION 14: Transport information

14.1 UN number

UN 1263

14.2 UN proper shipping name

Land transport (ADR/RID)

PAINT RELATED MATERIAL

Sea transport (IMDG)

PAINT RELATED MATERIAL (Basic Blue 7 derivate · Xanthene dye; CI.45160; similar C.I. Basic Red 1)

Air transport (ICAO-TI / IATA-DGR)

PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3
Classification code : F1
Hazard identification number (Kemler No.) : 30
Tunnel restriction code : D/E
Special provisions : LQ 5 I · E 1
Hazard label(s) : 3 / N

Sea transport (IMDG)

Class(es) : 3
EmS-No. : F-E / ~~S-E~~
Special provisions : LQ 5 I · E 1
Hazard label(s) : 3 / N

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3
Special provisions : E 1
Hazard label(s) : 3

14.4 Packing group

III

14.5 Environmental hazards

Land transport (ADR/RID) : Yes
Sea transport (IMDG) : Yes (P)
Air transport (ICAO-TI / IATA-DGR) : Yes

14.6 Special precautions for user

None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Use restriction according to REACH annex XVII, no. : 3, 40

National regulations

Water hazard class (WGK)

Classification according to AwSV - Class : 3 (Strongly hazardous to water)

15.2 Chemical safety assessment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stamping ink R 9
dark blue
Revision date : 03.08.2020
Print date : 05.08.2020

Version (Revision) : 17.1.1 (17.1.0)

No information available.

SECTION 16: Other information

16.1 Indication of changes

02. Labelling according to Regulation (EC) No. 1272/2008 [CLP]

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

See SECTION 2.1 (classification).

16.5 Relevant H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H360	May damage fertility or the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.